

3000 SERIES KING PIN Heavy Duty Step Deck



Standard Features:

102" overall width
Available in 30', 35', and 40' lengths*
*Straight back or plus beavertail
7' Step deck
14" I-Beam @ 26#/Ft. main frame
4" Channel cross members 18" O.C.
8" Channel side rail
Pierced frame
38" loaded deck height
2" x 8" Rough cut oak decking w/steel plate over wheels
5' Self-cleaning beavertail
(2) 19" x 60" Heavy duty loading ramps w/spring assist (With Beavertail)
50,000# Rated landing gear style jacks
(6) 1" Recessed D-Rings, welded to cross members
Side access steps, one per side
Fixed neck, King Pin style coupler (Set to specifications of tow vehicle)



Available with tandem 16,000# or 22,500# AL-KO Axles
Hubs: Oil Bath, 8-lug (16k) 10-lug (22.5k)
Suspension: Slipper spring (16k) Hutchens adjustable spring (22.5k)
Air brakes w/ABS (1S2M)
Wheels: 8-bolt duals (16k) 10-bolt duals (22.5k)
235 85R 17.5 16-ply radial tires

Soldered and shrink wrapped wiring
Junction box with breakers
Emergency breakaway switch w/gel cell battery
DOT approved sealed beam lighting (LED)
Breakaway w/gel cell battery (on electric brakes)
7-Prong round post socket (for use with tow vehicle jumper cord)
Glad hand sockets

Popular Options

Extended Step Deck Length (up to 10')
Steel Decking
Rub Rail & Stake Pockets
Spare Tire & Carrier



Effective 5/1/2011

Products & Features subject to change without notice