

ICH CG

Self-loading reel trailer



A "No-Frills" alternative to the standard ICH

Standard Features:

Overall Width: 102"
Overall Length: 144"
Maximum reel width: 70" on 7k, 64" on 10k
Maximum reel diameter: 120"
6" Channel mainframe & tongue
7,000# Top-wind drop leg jack
12 Gauge formed fenders
Open yoke design for easily loading/unloading
(2) Brand Hydraulics hand pumps independently operate
(2) 3" x 8" internally mounted hydraulic lift cylinders
Multi-position reel bar carrier
Secondary reel bar lock
2.5" Steel reel bar w/locking collars



Available with 7,000# or 10,000# stub axle
8-Lug Grease hubs
ST235 85R 16 10-ply radial tires (7k) 215 75R 17.5 16-ply radial tires (10k)
8-bolt 16" steel wheels (7k) 17.5" steel wheels (10k)
Electric brakes

3" Adjustable pintle eye (2-bolt)
7-Prong RV style light plug
Soldered and heat shrink wrapped wiring
DOT approved lighting (LED)
Breakaway switch w/gel cell battery
(2) 3/8" x 36" Safety chains
DuPont Corlar primer & DuPont Imron 5000 baked polyurethane top coat (White is standard)

Popular Options:

No options available on this model

More Photos Coming Soon