

IGT 100/200

Telescoping Pipe Carriers



Moves all types of plastic, steel, & concrete pipe

Standard Features:

Rear Telescoping (100) Front & Rear Telescoping (200)

Overall Width: 96"

Overall Retracted length:30' (100) 32' (200)

Overall Extended length:38' (100) 45' (200)

Empty Weight: 4,080# (100) 5,150# (200)

10" Channel Mainframe (100)

10" Channel double-boxed mainframe (200)

6" Channel cross members

Open floor pan

12 gauge formed fenders



(2) 7,000# AL-KO axles (100) (2) 10,000# AL-KO axles (200)

8-lug Grease Hubs

ST235 80R 16 10-ply radial tires (100) 215 75R 17.5 16-ply radial tires (200)

8-bolt 16" steel wheels (100) 8-bolt 17.5" super single steel wheels (200)

Electric brakes on both axles

24"H Full-width removable bulkhead

(4) 96" Pipe bolsters w/adjustable end posts

3" Adjustable pintle eye (4-bolt)

10,000# Spring-loaded drop leg front jack

(4) 4" x 27' Nylon straps w/fixed ratchets

Breaker bar and holder

(2) 3/8" x 36" Safety chains w/clasp

(2) 5" x 8" Rubber wheel chocks w/holders

7-prong RV style light plug

DOT approved light package (LED)

DuPont Corlar primer & DuPont Imron 5000 baked polyurethane top coat (White is standard)

Popular Options

Sliding stanchions on pipe bolsters

Expanded metal tool storage in tongue

Axle Upgrades (Call for details)

Coated pipe bolsters for pipe protection

Fleet paint colors (Shown Below)

