

# ***ILU-T***

## ***Tilt Deck Trailer***



### Standard Features:

102" Overall width  
80" between the fenders  
2" x 6" x 1/4" tubular mainframe  
6" channel tilting sub-frame  
3" channel cross members (16" O.C.)  
Available in full tilt or split deck models  
16', 18', 20' deck lengths (Including 2' steel approach)  
\*Max tilt portion is 20'. Max split deck is 24'  
5' Cold-formed tongue  
Hydraulic dampening cylinder  
2" x 8" Treated pine deck  
10,000# drop leg front jack  
12 gauge formed fenders  
Expanded metal tool storage in tongue  
Stake Pockets and rub rail



### Available with these Axle Packages:

9990# GVWR

(2) 5,200# capacity AL-KO 4" drop axles

6-bolt Grease hubs

ST225 75R 15 radial tires (8-ply)

Silver mod steel wheels (15" on 5,200# axles, 16" on 7,000# axles)

Electric brakes on both axles

14,000# GVWR

(2) 7,000# capacity AL-KO 4" drop axles

8-bolt Grease hubs

ST235 80R 16 radial tires (10-ply)

Adjustable 2 5/16" ball or 3" pintle eye coupler

7-prong RV-style light plug

Soldered and heat shrink wrapped wiring

DOT approved lighting (LED)

Emergency breakaway switch w/gel cell battery

(2) 3/8" x 36" safety chains

DuPont Corlar primer & DuPont Imron 5000 polyurethane top coat (Black is standard)

### Popular Options:

Rough Cut Oak Decking

12V Electric/Hydraulic Tilt

Removable Fenders

