



ILU-BT Removable Bin Trailer General Specifications

Effective 4/1/2009

Standard Trailer Features:

Available in 4, 6, 10, or 14 bin configurations
102" Overall Width
Aluminum tube and formed angle mainframe Construction
Front and Rear end panels constructed of .080 aluminum sheet
Strut assisted lid w/access doors constructed of .080 aluminum sheet
2" or 2 5/16" ball coupler (Based on capacity)
A-Frame tongue
2,000# front jack
(2) Adjustable rear stabilizer jacks
3,500# Dexter Axles
Torsion suspension
Electric brakes
ST205 75R 14 radial tires
5.5" x 14" Steel wheels w/ 5 on 4.5" bolt pattern
Soldered and shrink-wrapped wiring
DOT approved LED light package
4-prong light plug
(2) Safety chains, properly rated for trailer capacity
ADA Compliant 54" Fill Height

Bins:

42" w x 46" l x 48" h
Over 1 Cubic Yard Capacity
100% Polyethylene construction
Forklift -friendly
Nestable
American Made

Options

Cardboard Bin (Replaces 2 standard bins)
Hydraulic Surge brakes
Forklift bin rotator
Spare tire & carrier
Aluminum wheels
Aluminum bin lids (for free-standing bins)
Bin Dolly
Extra Bins
Rubber wheel chocks & holders

Can Custom Build to Your Specification

Images Coming Soon

Kiefer Industrial Trailers
Green Initiative
P.O. Box 88
Kanawha, IA 50447
1-888-254-3337 ext. 23

* Specifications Subject To Change